


# DUPLEX R5

compact ventilation units with the possibility of air circulation for ventilation, cooling and warm-air heating



## CP TOUCH CONTROLLER

touchscreen display



setting the modes, programming a unit operation

CP Touch controller

low voltage cabling



Internet access (as standard)

## DUPLEX RB5

Digital control module RD5 with web-server

Circular connecting ports 4 pcs

Exhaust air EC fan

Pre-filter e<sub>1</sub>

Counterflow heat recovery exchanger with efficiency up to **91 %**

Low-speed circulation EC fan

Optional evaporator for mechanical cooling or cooler for water cooling

Optional hot-water or electric heater

Filter G4 or F7 for recirculation air and supply air

Mixing and shutting flaps with servo drive

Filter G4 for exhaust air

Built-in, by-pass double valve with servo drive



RESIDENTIAL VENTILATION & HEATING

ATREA s.r.o., Čs. armády 32  
466 05 Jablonec n. Nisou  
Czech Republic



www.atrea.eu

Tel.: +420 483 368 111  
Fax: +420 483 368 112  
E-mail: atrea@atrea.eu

# ATREA VENTILATION AND HEATING SYSTEM

## ATREA VENTILATION AND HEATING SYSTEM

### System description

The HVAC system with the DUPLEX R5 series unit provides balanced ventilation with heat recovery in all the installation versions. The properly designed ventilation system provides fresh filtered air supply to each room and kitchen and at the same time, exhaust of effluent air from sanitary facilities, toilets, bathrooms, and kitchens. Owing to the unique system of inside air circulation throughout the object, it is possible to ensure afterheating after recovery, distribution of internal heat gains throughout the object, cooling or warm-air heating without necessity for an additional heating system.

The company ATREA offers this system as a complete construction set, consisting of the following main components:

- recuperative ventilation unit with air circulation of DUPLEX R5 series
- heat pumps and storage reservoirs
- the complete measurement and control system with the option to control other parts of the system (e.g. zone flaps, ground heat exchangers, etc.), including connection via internet
- the integrated system of ATREA air ducts and fittings suitable for all the required versions

### Use not only in low-energy and passive houses

Owing to the circulation circuit possibilities, utilisation consists in the wide scope of applications, in which DUPLEX R5 ensures balanced ventilation with heat recovery.

- Balanced ventilation and cooling – heating are ensured by the independent heating system, DUPLEX R5 connects the circulation circuit on request for distribution of gains from the fireplace or on request for cooling
- Warm-air heating, ventilation and cooling – the system with the DUPLEX R5 unit substitutes the heating system in rooms – thus it is the only HVAC system that meets a requirement for heating by means of air heating only. The customer selects an exchanger for the unit – low-temperature water exchanger (T) or electric exchanger (E).

### Design of DUPLEX R5 ventilation and heating system

The company ATREA prepared the detailed basis of project for designing of ventilation systems providing designers, together with catalogues of elements and the specialised design software, with all the necessary information for proper designing and dimensioning of ventilation and warm-air heating.

Based on the long-term measurements and experience with the implementation of the ventilation systems in the residential buildings, the ATREA company recommends dimensioning of the ventilation performance according to ČSN EN 15251 - Class 2 - see the marked part of the table below.

### Ventilation system advantages

- guarantee of necessary in terms of hygiene continuous air changes with the possibility of occasional increasing (e.g. by an external signal from W/C, bathroom, kitchen or other inputs according to the specific immediate requirements of users)
- saving up to 90 % of costs for the ventilation due to the high efficiency heat recovery exchangers
- exclusion of mould growth
- exclusion of thermal discomfort caused by the air supply with minimum temperature difference (again because of the high efficiency heat recovery)
- use of all internal and external heat gains from the apartment space for recuperative preheating of the ventilation air
- perfectly filtered air supply (through G4 or F7 filters) significantly limits the development of allergic and respiratory diseases of residents
- when setting the max. unit performance (through the by-pass), cooling in summer period is possible, mainly by night filtered air supply
- integrated modular system allows simple, also unassisted, installation

### Legislative requirements

The DUPLEX R5 units carry energy labels in accordance with EU Regulation no. 1253/2014 and 1254/2014.

### Ventilation performance

Standard – regulation		Ventilation intensity in unoccupied rooms (h <sup>-1</sup> )	Ventilation intensity (h <sup>-1</sup> )	Volume per person (m <sup>3</sup> /h)	Kitchens (m <sup>3</sup> /h)	Bathrooms (m <sup>3</sup> /h)	Toilets (m <sup>3</sup> /h)
CSN EN 15665 – Z1	Minimum value	0,3	0,3	15	100	50	25
	Recommended value		0,5	25	150	90	50
CSN EN 15251	1st Class	0,1 – 0,2	0,7	36	100	72	50
	<b>2nd Class</b>		<b>0,6</b>	<b>25</b>	<b>72</b>	<b>54</b>	<b>36</b>
	3rd Class		0,5	15	50	36	25
CSN 73 0540 – 2		0,1	0,3 – 0,6	15 – 25	References to other regulations		

### More documentation for designing a ventilation system




Marketing catalogue R5



Catalogue of components




www.atrea.eu



CD

Selection software

## HEAT RECOVERY – WHAT IS IT ?



### Heat recovery principle

Heat transfer occurs through the separating walls of a heat exchanger – in winter warmer exhaust air preheats colder supply air. The same principle is applied also in summer for cool recovery.

In winter time humidity condensates in exhaust air. This condensate increases heat recovery efficiency through improved heat transfer and is continuously drained into a sewer system.

### Significance of heat recovery

An energy-optimised heat recovery exchanger reaches a highly economical ratio between power consumption (to run fans), air performance and heat recovery.

The fan input vs. heat recovery gain ratio during ventilation reaches an energy efficiency of 17–25, i.e. from 1 W of power used to run a DUPLEX R5 up to 25 W is recovered from exhaust air.

**Effective ratio 1 : 25**

## DESCRIPTION OF DUPLEX R5 UNITS

### Purpose

The new 5th generation of recuperative DUPLEX units is available in two basic versions, as **DUPLEX RB5** in the ceiling design and as **DUPLEX RA5, RK5** in the upright design.

The units are intended for comfort ventilation and warm-air heating of all types of residential and public buildings, are particularly suitable for low-energy and passive houses and for flats in block of flats.

### Basic description


The unit housing, made with mineral insulation with the thickness of 30 mm ( $U = 0,81 \text{ Wm}^{-2}\text{K}^{-1}$ ), with suppression of thermal bridges and excellent sound deadening, is fitted with a swirling counterflow plastic heat recovery exchanger (efficiency up to 91 %), two ventilators of free impeller type with the electronic EC control, including control of a constant air flow, G4 filters of supply air as well as exhaust air before entering the recovery heat exchanger; an automatic by-pass flap, a control module and a connection terminal block. Condensate outlets are as standard prepared for the cooling version as well. Connection ports are circular, used for connecting flexible or fixed piping with suppression of thermal bridges. Access to the unit is possible through the openable hinged door via locking latches.

### Units advantages

- fans built-in as standard with an EC type free impeller are characterized by very low power consumption and excellent speed regulation

- higher outputs of the units enable occasional intensive air exhaust or summer ventilation
- recovery efficiency up to 91 % due to the new-generation counterflow recuperation exchangers
- excellent thermal insulation parameters of the unit housing with suppression of thermal bridges
- built-in by-pass is a standard part of the unit and needs no additional space; in addition, due to its construction, it ensures 100% by-pass in the by-pass mode without mutual thermal transfer
- standard control meets all the requirements of control, enabling the wide scope of connection of sensors and other inputs, control of shutting and zone flaps for distribution, control of heaters or the heating system of the house, etc., and furthermore, as standard, **includes a built-in web-server to enable control via internet**
- universal use from balanced ventilation, ventilation with circulation, circulation with heating and cooling
- option of a built-in type heater: low-temperature water exchanger (T) or electric exchanger (E).
- exchanger for direct (CHF) or water (CHW) cooling, option of two sizes - three-row and five-row

## CONDENSATE OUTLET




During the recovery, the heat recovery, moisture condensation occurs during the exhaust air cooling. Water condenses on the walls of the heat recovery exchanger; thereby further increasing the heat recovery efficiency. In the direction of the exhaust air flow, condensate flows from the recovery heat exchanger and is discharged from the DUPLEX unit into the sewer system. For the proper function and discharge, it is necessary to separate the unit and the sewer by a siphon with the sufficient height - min. 150 mm height is recommended. Small condensate discharge pumps can be used as well.

## COMPACT UNITS



A DUPLEX ALFA 5V or a KAPPA 5V unit provides a considerable simplification of design and erection works. It is the compact device with an air-water heat pump (4.8 kW) and heating mixing sets integrated in the DUPLEX RA5 or RK5 unit. Nobody on site is able to place all in such a small space. Problems with incorrect position of valves do not take place either; the result is interior equipment - decoration not only of technical rooms.

## R5 RECOVERY EFFICIENCY



## TECHNICAL DATA OF ERP DUPLEX R5

DUPLEX		RA5	RK5	RB5	
specific energy class	-	A <sup>1)</sup>	A <sup>1)</sup>	A <sup>1)</sup>	
specific energy consumption	SEC-W kWh/m <sup>2</sup> .a	-16,92	-16,74	-16,55	
	SEC-A kWh/m <sup>2</sup> .a	-40,82	-40,64	-40,57	
	SEC-C kWh/m <sup>2</sup> .a	-77,96	-77,77	-77,90	
maximum flow <sup>2)</sup>		m <sup>3</sup> .h	420	445	430
sound power level <sup>3)</sup>	L <sub>WA</sub>	dB	41	42	44

<sup>1)</sup> All types of the regulation built-in in the unit standardly include a minimum of two inputs for connecting electrical signals arising as a result of human manipulation with lighting, or for connecting other devices that automatically regulate the unit output. These inputs must always be connected, or other types of sensors (e.g. CO<sub>2</sub>, VOC, rH and the like) must be connected instead.


<sup>2)</sup> The maximum flow rate is set at the pressure disposition of 100 Pa

<sup>3)</sup> The stated value refers to the reference flow rate i.e. 70 % of the maximum flow rate, and to the pressure disposition of 50 Pa

# DIMENSIONS AND DESIGN

## R5 DIMENSIONS AND DESIGN


### DUPLEX RA5



#### Version

10/0

11/0




#### Port configuration

10/1


10/2

10/3




Similarly, this is also possible in port configurations 11/1, 11/2, 11/3.

### DUPLEX RK5



10/0


11/0



10/1


10/2

10/3




Similarly, this is also possible in port configurations 11/1, 11/2, 11/3.

### DUPLEX RB5




30/0

31/0



30/1

31/1



- ⊙ port position in design x/0
- ① port position in design x/1 - this is performed on site by turning the fan to a prepared position.

Note: Top view - plan view

#### LEGEND


e <sub>1</sub>	fresh air inlet	UT	connection of heating water (T) or electricity (E)
c <sub>1</sub>	circulation air inlet	CHF	connection of mechanical cooling
c <sub>2</sub>	outlet of circulation air and fresh air	CHW	connection of water cooling
i <sub>1</sub>	exhaust air inlet	RM	digital control module RD5
i <sub>2</sub>	exhaust air outlet		
K	condensate outlet		

#### WEIGHT AND CONNECTION


DUPLEX		RA5	RB5	RK5
diameter of connection ports	mm	∅ 160 / ∅ 200	∅ 160 / ∅ 200	∅ 160 / ∅ 250
weight [according to equipment]	kg	115 - 125	87 - 97	125 - 135
condensate outlet	mm	2x ∅ 16		
UT, CHW connecting pipes	mm	20 / 20		
CHF connecting pipes	mm	12,7 / 6,35		

## CIRCULATION AIR FAN


### DUPLEX RA5






### DUPLEX RB5



### DUPLEX RK5



## EXHAUST AIR FAN




### Legend:


- $Q_{ref}$  reference flow \*\*
- $Q_{max}$  maximum flow \*\*

- \* max. pressure reserve curve is indicated
- \*\* electrical power consumption of the entire unit (both fans including the regulation) is indicated at the same flow in the ventilation mode


## DIRECT EVAPORATOR (CHF.3)




## 3-ROW WATER COOLER (CHW.3)



## HOT-WATER HEATER (T.3)



## 5-ROW WATER COOLER (CHW.5)





# CONTROL SYSTEM

## RD5 DIGITAL CONTROL SYSTEM

### Basic description

Digital control module type RD5 is the most advanced method for the unit control. It provides all the basic functions and also includes a number of other inputs and outputs for connecting with optional sensors (e.g. CO<sub>2</sub> sensors, relative humidity sensors), signals from the rooms (WC, bathroom, kitchen), the heating systems including the shut-off valves or the shut-off butterfly valves in the distribution system. In addition, it includes the **web-server** and the **Internet access**.

The units with the digital module can be controlled:

- Via the CP Touch controller with a touch display,
- Via the intelligent built-in web-server – allows controlling and set-up via a web application, and is possible also for the options a),
- Via a foreign control system via a standard interface Modbus TCP.

### Functions

The control module provides all the basic functions of the unit:


- programming of the various outputs of ventilation, heating and cooling during the day and the week
- continuous output control of both fans with the constant flow function
- automatic control of the by-pass butterfly valve (supply air by-pass) according to the outside air temperature
- control of various heat sources on request for afterheating or heating of rooms with separate control of temperature in bathrooms
- control of cold sources – ground exchangers and heat pumps on request for cooling, with protection against going below minimum temperature of supply air
- the recovery exchanger frost protection
- switching to the selected output when closing through the external signal (e.g. from WC, bathroom, kitchen) with optional start and run-down
- control of the shut-off butterfly valve at the inlet and the exhaust, and also two zone ventilation butterfly valves and one exhaust butterfly valve from the kitchen (the butterfly valves are not part of the unit) – 24 V DC

- continuous control of circulation (mixing) flap
- optional automatic operation controlled by sensors – CO<sub>2</sub> concentration, relative humidity or VOC (optional accessory) – 0–10 V input or switching contacts
- according to the settings, the unit allows periodic ventilation mode – the unit is at rest and switches ventilation at set intervals
- automatic setting of the ventilation length depending on the number of persons and the building airtightness – at the periodic ventilation or when running the intermittent ventilation


**CP Touch controller:** The modern, wall mounted CP Touch controller is intended for setting the basic ventilation and circulation modes and displaying the status of the ventilation unit including the indication of fault conditions.

It allows the user access to common functions or programming of the operating modes that can be operated in the manual mode or the automatic mode according to the weekly program settings. The controller also allows setting a temporary party / holiday mode. Part of the controller is an integrated room thermostat with a weekly heating/cooling program, which can also control the simple heating system by using the functions of the control module. All values can be set on the well structured graphical touch screen.


### CP Touch



## CONTROL AND ENERGY SYSTEMS FOR HEATING AND HOT SERVICE WATER HEATING



### DUPLEX RB5-T-CHW



### DUPLEX RB5-T-CHF

The integrated heat accumulator IZT (e.g. IZT-U-TTS 650) for combined preparation of hot water (HW) and central heating (CH) by means of electric coils with solar support or connection to the heat pump (HP).


The double exchanger is intended for flow-through heating of hot water, excluding occurrence of Legionella germ and corrosive sludge, presence of which is common in storage boilers.

The bottom exchanger is connected to the solar system. The heat accumulator IZT can also be connected to biomass boilers or heat pumps, where the condensing unit provides heating or cooling, IZT serves as a bivalent source. It is not necessary to realise all the described sources at the same time.

An electric or a condensing boiler burning natural gas, with a built-in hot water heater or a separate hot water reservoir. Gas boilers with the built-in output modulation depending on water temperature, providing a continuous change of the boiler output in the range from 15 to 100 %. The prospective outdoor condensing unit with the option of reverse operation makes it possible, in connection with the basic and the additional control DUPLEX RB5, to cool interior during summer season and heat interior during transition periods (spring, autumn) – systems of air-air heat pumps.


## DUPLEX R5 UNIT OPERATION MODES

1




### Balanced ventilation mode

all-year period  
 $n_v = 0,15 - 0,5 / h^{-1}$   $n_c = 0 / h^{-1}$   
 Balanced ventilation with adjustable output from 75 to 440 m<sup>3</sup>/h, with recovery or via the by-pass. It is intended for ventilation and afterheating (without circulation) in the transition period.  
 Both fans in operation, the mixing flap closed.




2




### Circulation heating and ventilation mode

Heating period  
 $n_v = 0,15 - 0,5 / h^{-1}$   $n_c = 0,5 - 1,5 / h^{-1}$   
 Warm-air circulation heating and balanced ventilation with waste heat recovery with circulation output up to 800 (850, 1400 depending on R5 type) m<sup>3</sup>/h (at 150 Pa) and ventilation output up to 420 / 430 / 445 m<sup>3</sup>/h (at 150 Pa)  
 Both fans in operation, the mixing flap mixes outdoor air and circulating air:




3




### Circulation heating mode with intermittent ventilation

Heating period  
 $n_v = 0$   $n_c = 0,5 - 1,5 / h^{-1}$   
 The basic recommended operation mode of circulation heating. When persons are present, an impulse from the WC and the bathroom occasionally switches the exhaust fan with an adjustable run-down, an impulse from the kitchen switches to the mode No. 1 without run-down. If appropriate, ventilation is periodically switched at a set interval. All of them with recovery. When mechanical cooling is realised, this mode is also used for heating by means of the air-conditioning unit in the transition period (spring, autumn).




4




### Overpressure ventilation mode

Summer season  
 $n_v = 0,5 - 2,0 / h^{-1}$   $n_c = 0 / h^{-1}$   
 The intensive summer overpressure ventilation of residential premises by fully supplying outdoor air, prospectively from the ground heat exchanger. It can also be used for night precooling.  
 Air outlet through a slightly open door.  
 The effluent air fan is activated by an impulse, the mixing flap in the position „2“, the by-pass flap is opened.




5




### Circulation cooling mode with ground heat exchanger (ZVT-c; ZVT-s)

Summer season  
 $n_v = 0 / h^{-1}$   $n_c = 0,5 - 1,5 / h^{-1}$   
 The intensive summer circulation cooling of residential premises by interior air, circulating through the ground heat exchanger. The effluent air fan is activated by an impulse, the mixing flap in the position „2“, the by-pass flap is opened.  
 This can only be in connection with realisation of the circulation ground exchanger of an air or an anti-freezing liquid type.




5a



### Mechanical circulation cooling mode

Summer season  
 $n_v = 0 / h^{-1}$   $n_c = 0,5 - 1,5 / h^{-1}$   
 The intensive circulation cooling of residential premises in connection with the outdoor condensing unit („mechanical cooling“). When persons are present, an impulse from the bathroom and the WC occasionally switches the ventilation fan with an adjustable run-down. An impulse from the kitchen switches to the mode No. 1 without run-down. In this case, cooling is not enabled. If appropriate, ventilation is periodically switched at a set interval.






$c_1$  ..... inlet of circulation air from rooms to the unit  
 $c_2$  ..... outlet of heating air, cooling air and fresh air from the unit to rooms


$e_1$  ..... inlet of fresh outdoor air  
 $i_1$  ..... inlet of effluent air from sanitary facilities to the unit  
 $i_2$  ..... outlet of effluent air from the unit

# ATREA MODULAR HVAC SYSTEM


## DUPLIX R5 UNITS

	<b>DUPLIX RA5 800 / 420</b>	Ord. No. A170421
	<b>DUPLIX RB5 800 / 430</b>	Ord. No. A170431
	<b>DUPLIX RK5 1400 / 440</b>	Ord. No. A170441

## FILTERS


	<b>FT RB4 G4 – circulation</b>	Ord. No. A170922
	<b>FT RB4 F7 – circulation</b>	Ord. No. A170923
	<b>FTU RB4 – circulation carbon</b>	Ord. No. A170929
	<b>FT RB4 G4 – exhaust</b>	Ord. No. A170926
	<b>FT RA3 G4 – circulation (RA3, RK3, RA4, RK4, RA5, RK5)</b>	Ord. No. A170912
	<b>FT RA3 F7 – circulation (RA3, RK3, RA4, RK4, RA5, RK5)</b>	Ord. No. A170913
	<b>FTU RA3 – circulation carbon (RA3, RK3, RA4, RK4, RA5, RK5)</b>	Ord. No. A170928
	<b>FT RA4 G4 – exhaust (RA4, RK4, RA5, RK5)</b>	Ord. No. A170920

Spare filter fabrics are delivered in a 5 pc pack.

	<b>FK RB4 G4 – circulation</b>	Ord. No. A170924
	<b>FK RB4 F7 – circulation</b>	Ord. No. A170925
	<b>FK RB4 G4 – exhaust</b>	Ord. No. A170927
	<b>FK RA3 G4 – circulation (RA3, RK3, RA4, RK4, RA5, RK5)</b>	Ord. No. A170914
	<b>FK RA3 F7 – circulation (RA3, RK3, RA4, RK4, RA5, RK5)</b>	Ord. No. A170915
	<b>FK RA4 G4 – exhaust (RA4, RK4, RA5, RK5)</b>	Ord. No. A170921

Spare filter cassettes are delivered in a single-piece package.

## OPTIONAL ACCESSORIES - WATER HEATER

	<b>Modification T - water heater RA5</b>	Ord. No. A170422
	<b>Modification T - water heater RB5</b>	Ord. No. A170432
	<b>Modification T - water heater RK5</b>	Ord. No. A170442



## OPTIONAL ACCESSORIES - WATER COOLER

	<b>Modification CHW – water cooling RA5, 3-row</b>	Ord. No. A170424
	<b>Modification CHW – water cooling RA5, 5-row</b>	Ord. No. A170425
	<b>Modification CHW – water cooling RB5, 3-row</b>	Ord. No. A170434
	<b>Modification CHW – water cooling RB5, 5-row</b>	Ord. No. A170437
	<b>Modification CHW – water cooling RK5, 3-row</b>	Ord. No. A170444
	<b>Modification CHW – water cooling RK5, 5-row</b>	Ord. No. A170445







## OPTIONAL ACCESSORIES - DIRECT COOLER

	<b>Modification CHF – mechanical cooling RA5</b>	Ord. No. A170426
	<b>Modification CHF – mechanical cooling RB5</b>	Ord. No. A170438
	<b>Modification CHF – mechanical cooling RK5</b>	Ord. No. A170446

## CONTROLLERS

	<b>CP Touch controller</b> – touchscreen – 4 color versions (white, ivory, grey, anthracite)	Ord. No. A170130 Ord. No. A170131 Ord. No. A170132 Ord. No. A170133
	<b>ADS 100 ABB</b>	Ord. No. A170258



## OPTIONAL ACCESSORIES - 0-10 V DIGITAL INPUT

	<b>ADS RH 24</b> room relative humidity sensor	Ord. No. A142318
	<b>ADS SMOKE 24</b> room cigarette smoke and air quality sensor	Ord. No. A142311
	<b>ADS VOC 24</b> room air quality sensor	Ord. No. A142331
	<b>ADS CO<sub>2</sub> 24</b> room sensor controlling the ventilation performance based on the current CO <sub>2</sub> value	Ord. No. A142319
	<b>ADS CO<sub>2</sub> D</b> channel sensor controlling the ventilation performance based on the current CO <sub>2</sub> value	Ord. No. A142330
	<b>ADS RH D</b> channel relative humidity sensor	Ord. No. A142332


## OPTIONAL ACCESSORIES - CONTACT INPUT

	<b>HYG 6001</b> room hygrostat – relative humidity sensor	Ord. No. A142303
---	--	------------------


## OPTIONAL ACCESSORIES - MECHANICAL COOLING

	<b>ATREA FG09 (RB5)</b> outdoor condensing unit	Ord. No. A400010
	<b>ATREA FG14 (RA5, RK5)</b> outdoor condensing unit	Ord. No. A400015
	<b>ATREA FG18 (RK5)</b> outdoor condensing unit	Ord. No. A400019
	<b>DMCH – ATW (FG09)</b> additional control module	Ord. No. A170511
	<b>DMCH – ATW (FG14)</b> additional control module	Ord. No. A170512
	<b>DMCH – ATW (FG18)</b> additional control module	Ord. No. A170513

## OPTIONAL ACCESSORIES - ELECTRIC HEATER

	<b>Modification E – electric heater RA5</b>	Ord. No. A170423
	<b>Modification E – electric heater RB5</b>	Ord. No. A170433
	<b>Modification E – electric heater RK5</b>	Ord. No. A170443

## OPTIONAL ACCESSORIES - ZONE FLAP

	<b>Zone flap including servo drive for RA5 / RK5</b> it can only be used with distribution chamber R111011 and R111010	Ord. No. A170427
--	---	------------------