

<b>Comfort Series AE</b>	<b>Model</b>	<b>PASRW010</b>	<b>PASRW015</b>	<b>PASRW020</b>	<b>PASRW030</b>	<b>PASRW035</b>	<b>PASRW040</b>
Heating Capacity (27°C/24.3°C)	kW	4.12	5.95	8.47	11.6	13.7	17.3
	Btu/h	14008	20230	28798	39440	46580	58820
Heating Power Input	kW	0.73	1.04	1.45	1.98	2.41	3.02
COP		5.64	5.72	5.84	5.86	5.68	5.73
Running Current	A	3.4	4.8	6.5	9.1	11.0	13.8
*Heating Capacity (24°C/19°C)	kW	3.82	5.36	7.74	10	12.5	15.5
	Btu/h	12988	18224	26316	34000	42500	52700
*Heating Power Input	kW	0.75	1.05	1.48	1.90	2.36	2.90
*COP		5.09	5.10	5.23	5.26	5.30	5.34
*Running Current	A	3.5	4.9	6.6	8.7	10.8	13.3
**Heating Capacity (15°C/12°C)	kW	3.05	4.25	6.01	8.02	9.8	12.4
	Btu/h	10370	14450	20434	27268	33320	42160
**Heating Power Input	kW	0.74	1.00	1.40	1.80	2.17	2.73
**COP		4.12	4.25	4.29	4.46	4.52	4.54
**Running Current	A	3.4	4.6	6.3	8.2	9.9	12.5
Power Supply		230V~/50Hz					
Compressor Quantity		1					
Compressor		Rotary					
Fan Quantity		1					
Fan Power Input	W	90	90	90	120	120	150
Fan Rotate Speed	RPM	850	850	850	850	850	850
Fan Direction		Horizontal					
Noise (10 meter)	dB(A)	37	38	42	42	42	44
Noise (1 meter)	dB(A)	48	50	52	54	54	56
Water Connection	mm	50	50	50	50	50	50
Water Flow Volume	m3/h	1.5	2.3	3	4.5	5.3	6
Water Pressure Drop (max)	kPa	2	2.4	3.2	3.5	10	15
Main Unit Net Dimensions(L/W/H)	mm	770x315x585	770x315x585	953x360x605	953x360x605	953x360x605	1115/470/870
Main Unit Shipping Dimensions(L/W/H)	mm	785x325x585	785x325x585	970x370x615	970x370x615	970x370x615	1220/480/880
Water temp(in):26°C;							